



## NOVO COLOR TOP

Colored Dry shake surface hardener for stamped concrete

### DESCRIPTION

**Novo Color Top** is a ready to use dry shake color hardener. **Novo Color Top** is formulated to be easily integrated into the surface of the freshly placed concrete. **Novo Color Top** consists of a special grade of very hard wearing aggregates, cement, additives for high workability and pigment. **Novo Color Top** easy to apply to fresh wet concrete by hand trowel, mechanicals trowel and stamps forms. Regarding the monolithic property, it is easy to avoid the problems of thin screeds such as, shrinkage curling and etc...

### USES

**Novo Color Top** is regularly used as a floor hardening and coloring agent with flat work and stamped concrete to stimulate the look of brick stone, tile, slate, etc. **Novo Color Top** is also used in institutional, industrial, commercial and residential applications for flat concrete floors where abrasion resistance and colored floor is desired.

### ADVANTAGES

**Novo Color Top** provides hard, durable, abrasion resistance hardscapes.-it offers streak-free, uniform color in a wide color selection.  
-Due to its dense surface, **Novo Color Top** is longer wearing, easier to maintain, and more resistance to the effects of freeze/thaw cycles.  
-Special colors according to customer needs

### PACKAGE

**Novo Color Top** is supplied in 25 Kg double P.E. bags.

### COVERAGE

3 Kg/m<sup>2</sup> Light duty.  
5 Kg/m<sup>2</sup> Medium duty  
7 Kg/m<sup>2</sup> Heavy duty.

### BASE CONCRETE

-The same plant should batch all concrete to avoid variation.  
-All concrete should be placed at the same slump.  
-Concrete should be placed and screeded with normal procedures  
-At this point the concrete should be floated with a wood or magnesium bull float.

### APPLICATION :

- after initial floating and all excess bleed water has dispersed, broadcast first application of **Novo Color Top** using about 60% of recommended amount and let it remain on the surface for several minutes or until **Novo Color Top** has wetted out sufficiently, then float with a wood or magnesium float. Immediately broadcast the second application with remaining of **Novo Color Top** and let it wet out for several minutes then trowel it.

#### Non Skid Finish:

to achieve a non skid finish, broadcast second application of **Novo Color Top** and do not trowel or work into concrete, let it sit for a few minutes or until ready to stamp, apply release powder and stamp as usual, this will produce a more textured nonskid surface. After the concrete has achieved it's setting the release agent may be removed by pressure rinsing with a high power pressure cleaner, or a soap and water solution and scrubbed with a broom.

#### Sealer:

to protect and help cure the concrete, two coat of **Novo Guard clear** sealer are recommended.

### HEALTH AND SAFETY

- Wear protective cloths, gloves, glasses and face protection.
- For skin contact, remove it by soap and clean water .
- For eye contact rinse with plenty clean water and then seek medical advice.
- For more details, require safety data sheet for the product.

#### **Disclaimer**

The provided technical information is given to the best of our knowledge and is based on extensive testing. As the information herein is of general nature, this given information will not expressed or implied as a warrantee involving any act of liability in case of misapplication. A trial should be implemented to ensure that this product confirms to the required conditions for usage