

High Quality Acrylic Coating

DESCRIPTION

Novo Cryl is high quality one component coating that based on special acrylic resin. It is used as a good protection for building materials such as concrete, gypsum, metal, brickwork, and asbestos.

ADVANTAGES

- Easy to apply, dry quickly and cling to the damp and chalky surfaces without peeling or flaking.
- Complete protection from damp attack of most oils and chemicals and high abrasion resistance.
- Good yellowing resistance.
- Good weathered resistance
- It is suitable for inside and outside application.
- Good chemical resistance.
- Suitable as an anti- fungus and anti-bacteria paint. It can be used in drinking water tanks and food stores.

PROPERTIES @ 25 C °

Color	White , grey , all required colors
Gloss	semi-gloss
Solid content by Weight	54 ± 2 %
Specific gravity	1. 35 ± 0.05 g/cm ³
Touch dry	20 – 30 min
Hard dry	24 hrs.
Shelf life	12 months in suitable storage conditions
Rate of use	4 -6 m ² /kg -/ 100 μ DFT (depending on the surface conditions)

DIRECTIONS FOR USE

- Clean surfaces from dust, oils and grease.
- Apply **Novo Cryl** by a soft brush or Spraying (recommended spraying application)
- In case using spraying system, adjust the required viscosity by thinning by **Novo Sol X2 Or Novo Sol 13** (5-10)%
- Applying subsequent coats should be after 5- 8 hours depending on weather conditions temperatures and ventilations.
- Apply one or more coats depending on the porosity of the surface and the degree of resistance required.
- Clean tools by Novo **SOL T 09**

STORAGE

One year under suitable storage conditions. (10 – 25) C°

PACKING

- 20 kg & 4 kg
- (as customer require)

HEALTH AND SAFETY

- Wear protective clothes, gloves, glasses and face protection.
- Good ventilations in case of spraying application.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.
- For eye contact, rinse with plenty clean water then seek to medical advice.