

Novo Latex Sealer

Data Sheet

Last update: - 15 / 5 / 2018 (1)

Emulsion Sealer primer.

DEFINITION

Novo Latex Sealer is an emulsion Sealer primer based on special emulsion polymer for interior and exterior use

ADVANTAGES

1. Ready to use and easy to apply with its enhanced properties
2. give a smooth finish to walls before putty application
3. Can be used as an under layer for all types of paints and wall papers.

FIELDS OF USE

- As a primer sealer with superior sealing properties.
- Most suitable for internal and external use on cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
Color	Milky white
Glossy	Matt
Density	(1.20 ±0.05) kg / L
Viscosity	15 – 20 Poise
PH	8- 9
Coverage	5– 7 m ² / kg (depending on surface conditions)
Shelf life	12 months (under suitable storage conditions)

SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. Mix the product well before application
3. Apply one coat or more by brush , roller or spray

Guide coating system for Interior and Exterior

Primer Sealer	Novo Latex Sealer	1 Coat
Putty	Novo Putty	2 Coats

STORAGE CONDITIONS

Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed. (10 -30) C°

PACKING

- Plastic pail : 4 & 15 Kg (As customer require)

PRECAUTIONS & SAFETY

- **Novo Latex Sealer** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.