

Novo Super Flat

Data Sheet

Last update: - 15 / 5 / 2018 (1)

Interior & Exterior high quality plastic 1 / 4 gloss paint

DEFINITION

Novo Super Flat is high quality flat emulsion paint based on special Acrylic polymer, Titanium dioxide and special fillers which are a flat finish coat for interior and exterior use.

ADVANTAGES

- **1.** Easy apply.
- 2. High abrasion resistance.
- **3.** Washable emulsion paint.
- **4.** Adheres well and can be applied on all surfaces of building.
- **5.** White and colored to suit all tastes.

FIELDS OF USE

- 1. Use for cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.
- **2.** Suitable for homes, schools, hospitals, office building, hotels ...etc.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
Color	White and colored
Glossy	1/4 gloss
Density	$(1.30 \pm 0.05) \text{ kg / L}$
Viscosity	20-30 poise
PH	8-9
Coverage	$9 - 10 \text{ m}^2 / \text{kg}$ (depending
	on surface conditions)
Shelf life	12 months (under suitable
	storage conditions)

SURFACE PREPARATION

- 1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
- 2. The surface should be sealed by **Novo Latex Sealer** if required.
- 3. Apply one or more coat Novo putty to smoothing the surface.
- 4. Cavities can be filled with **Novo putty**.
- 5. Apply one coat of Novo under coat (Novo Eco)

DIRECTIONS OF USE

Mixing before use

Novo Super Flat should be mixed well before using to obtain homogenous liquid.

Applications:

- Apply one or more coats of Novo Super Flat by suitable roller, brush or spray
- Novo Super Flat can be diluted with clean water
 1 5 % if required to facilitate the application.

Guide coating system for Interior and Exterior

Primer Sealer	Novo Latex Sealer	1 Coat
Putty	Novo Putty	2 Coats
Under Coat	Novo Eco	1 Coat
Finish Coat	Novo Super Flat	1-2 Coat

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight. (10-30) C°

PACKING

- Plastic pail: 20 Kg & 10 Kg & 5 Kg
- Steel pail: 15 liter (as customer require)

PRECAUTIONS & SAFETY

- Novo Super Flat is non flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.